

SERVOPRO

NanoTrace DF-760E

Product overview

High Purity



Gas	Measures	Application
Moisture	ppm	Quality
Oxygen	Trace ppb Ultra trace ppt	



SENSING TECHNOLOGY

Laser Moisture



Coulometric



Key applications

- Ultra high purity bulk gas quality control checks for small line width semiconductor fabs
- Process line leak detection within semiconductor carts

Unique dual measurement trace/ultra-trace moisture/oxygen analyzer for quality control of UHP bulk gases

Unrivalled performance

- Uses industry-leading, high stability Tunable Diode Laser Absorption Spectroscopy (TDLAS) sensing technology
- 100ppt LDL (H₂O) / 45ppt LDL (O₂)
- Servomex has 70 years' experience pioneering gas analysis with thousands of this product line in the field

Flexible

- Analysis resistant to gas cell contamination: DF-760E operates to specification with up to 90% signal loss
- Storage and recall function: calibration, system error and measurement data facilitates archiving operational history
- Broad Detection Range:
0-20ppm – 0-2ppb min (H₂O) /
0-20ppm – 0-1ppb min (O₂)

Easy to use

- Dual analysis capability provides 'one-box' solution for H₂O / O₂ trace contaminant measurements
- A single analyzer can be used for multiple background gases: N₂, H₂, He, Ar and O₂

Low cost of ownership

- Resilient TDLAS and non-depleting Coulometric sensing requires minimal ongoing maintenance
- Negligible sensor drift greatly extends calibration intervals

Benchmark compliance

- IEC 61010-1
- Overvoltage Category II, Pollution Degree 2
- EU EMC Directive
- EU Low Voltage Directive
- Class 1 laser product

For more information visit servomex.com/contact

SERVOPRO

NanoTrace DF-760E

Product overview

High Purity

High stability TDLAS trace/ultra-trace measurements

Ultra-trace qualification of UHP electronic gases is essential for semiconductor fabrication. You need a moisture analyzer that can deliver highly accurate measurements sensitive to perturbations, but limits production-disrupting false positives. The lowest LDL is a must, and with our dynamic pressure Herriott Cell your LDL stays the same no matter what background gas you choose. So make sure to check the LDL for all the gases of our competition, as their LDL claims will not be consistent.

A no compromise solution

The DF-760E is designed to meet the exceptional gas purity standards demanded by semiconductor manufacturers worldwide. It utilizes leading-edge, non-depleting TDLAS and Coulometric sensing technologies, housed in a robust and resilient new electronics package. The result is an analyzer that delivers an ultra-sensitive, industry-leading 100ppt Lower Detection Limit, ideal for checking for minute levels of moisture in a wide range of UHP electronics-grade gases, including N₂, H₂, He, Ar and O₂. Measurement data is recorded and readily available through flexible storage and recall functions, the DF-760E is the complete solution for UHP gas monitoring in 300mm semiconductor fabs.

Field repairable and reduced ongoing costs

The new DF-700 Series Gen VII was designed for manufacturability and repairability. The laser cell, hard drive, CPU, PCBs, display, filter and gas panel can now all be replaced in the field. We have SOPs and service videos to guide these repairs. So in the rare case a unit exhibits a component failure, the product can stay in your facility to be repaired by a competent technician of yours or ours.

The use of patented, leading-edge TDLAS technology provides long-term stability and accuracy, while the use of this first principle physics method also helps to reduce ongoing maintenance thanks to its non-depleting nature.

These analyzers are not intended for any form of use on humans and are not medical devices as described in the Medical Devices legislation or regulation.

Please note: Whilst every effort has been made to ensure accuracy, no responsibility can be accepted for errors and omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines. This document is not intended to form the basis of a contract.

Servomex has a policy of constant product improvement and reserves the right to change specifications without notice. © Servomex Group Limited. 2024. A Spectris company. All rights reserved.

Useful links:



servomex.com/service



servomex.com/systems



servomex.com/expert-guidance





Specifications

Gases measured	H ₂ O and O ₂	
Technology	Tunable Diode Laser Absorption Spectroscopy (TDLAS) and Coulometric	
Performance		
Gas	H₂O	O₂
Background gases	N ₂ , O ₂ , H ₂ , He and Ar	N ₂ , H ₂ , He and Ar
Technology	Tunable laser diode (TDL)	Coulometric
Measurement range	0-20ppm - 0-2ppb minimum	0-20ppm - 0-1ppb minimum
Lower detection limit	100ppt	45ppt
Intrinsic error (accuracy) FS	±3% of reading / ±0.2ppb (whichever is greater)	±3% of reading / ±0.1ppb (whichever is greater)
Response time (T₉₀)	<3 minutes at 1 l/min	<15 seconds at 1 l/min
Zero drift/month	Negligible	
Smallest recommended output range	0-2ppb minimum	0-1ppb minimum
Upset recovery time	<5 minutes to return to within 10ppb of previous stable reading	
Signal outputs/inputs		
Analog output	4 output options available for both O ₂ and H ₂ O Isolated 4-20mA dc and a choice of 0-1, 0-5 or 0-10V dc (analog output freeze control during calibration)	
Analog output range	Output parameters H ₂ O scalable to any range between 0-2ppb to 0-20ppm O ₂ scalable to any range between 0-1ppb to 0-20ppm	
Visual alarms	Various alarms available 4 moisture levels, temperature, system error, pressure range and hydrogen safety system (if applicable) 4 O ₂ levels, temperature, low electrolyte, low flow, low bypass flow, service in progress	
Dual scale range	2 user selectable analog output ranges	
Relay contacts	4 non-latching, independently assignable relays per measurement. SPDT contacts rated for 1A at 30 VDC	
Serial communications	Factory configured RS232 or RS485 two-way serial communications	
Sample conditions		
Sample flow	1 l/min H ₂ O and 500 ml/min O ₂ (contact Servomex for other gases)	
Bypass flow	0.25 to 2.5 l/min	
Pressure	30 to 150psi, 2.07 to 10.34 Bar, 207 to 1,034 KPa	
Dew point	+5°C (+9°F) below minimum ambient	
Temperature	+10°C to +80°C (+50°F to +176°F)	
Particulates	Filtered to 2µm	
Condition	Sample must be oil free, non-corrosive, non-condensing, no solvents, alcohols or aldehydes. Must be free of acidic components - contact Servomex for sample preconditioning options.	
Vent	Vent to atmosphere	

Operating environment	
Temperature	Operating: +10°C to +40°C (+50°F to +105°F) Storage: Less than +50°C (122°F)
Warm up time	5 minutes
Relative humidity	0 to 95% RH non-condensing
Operating altitude range	0-2,000m above sea level
Physical	
Size	483mm (19") Wide x 266mm (10.5") High x 631mm (24.84") Deep
Weight	33.2kg (73lbs)
Aspirator vacuum source	Aspirator with 1/4" compression inlet and outlet fittings
Mounting	19" rack mount NEMA 1 enclosure
Sensor storage conditions	We recommend that the analyzer be operated as intended within 6 months of delivery
Utilities	
Supply voltage	110V ac at 5A or 230V ac 50/60 Hz @ 2.5A
Standard aspirator gas supply (gauge)	N ₂ or CDA at 80psig (+/- 3psig), 15 l/min with a back-pressure on outlet stream of <2psig
Pneumatic gas (gauge)	N ₂ or CDA 60 to 100psi, 4.14 to 6.89 Bar, 413.7 to 689.5 KPa

Options

Configuration options		
Power input	110 VAC input power	☐
	220 VAC input power	☐
Hydrogen safety system	Not required	☐
	System with pump purge	☐
	System without pump purge	☐
Vacuum source	Aspirator (standard)	☐
	Pump	☐
Key lock	Not required	☐
	Required	☐
Communication	Not required	☐
	RS232 communication	☐
	RS485 communication	☐
Special analog output	Analyzer supplied with isolated 4-20mA and a choice of	
	0-1 VDC	☐
	0-5 VDC	☐
	0-10 VDC	☐
Power cord	Not required	☐
	USA	☐
	Europe	☐
	UK	☐
Electrolyte type	Gold	☐
Electrolyte shipment method	None required, has own stock	☐
	From factory (add line item)	☐
	Other Servomex plant (add line item)	☐

Please tick the box for required options



Compliance

EC directives	This product complies with the EU EMC Directive, EU Low Voltage Directive, Pollution Degree 2. This is a class 1 laser product.
Electrical safety	Electrical safety to IEC 61010-1


Sample wetted materials

Analyzer fitted with	Stainless steel G10 Epoxy Polypropylene PCTFE
----------------------	--

Dimensional drawings



Dimensions shown in millimetres [inches]



We're ready to help

Whatever your gas
analysis requirements,
wherever you are.

These analyzers are not intended for any form of use on humans and are not medical devices as described in the Medical Devices legislation or regulation.

Please note: Whilst every effort has been made to ensure accuracy, no responsibility can be accepted for errors and omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines.

This document is not intended to form the basis of a contract.

Servomex has a policy of constant product improvement and reserves the right to change specifications without notice.

Analysis that **empowers**

© Servomex Group Limited. 2024. A Spectris company.
All rights reserved.

PBTDSDF760 Rev. 5 Date: 10/24

SERVOMEX 
a **spectris** company